LUCIFER FURNACES



Manufacturer of Industrial Heat Treating Furnaces and Ovens

Red Devil Series - Economy Dual Chamber Furnaces



Low Cost - Top Quality

Two chambers in one complete "Space Saving" package to harden, draw and quench. The upper chamber is rated for operation to 2200°F. The lower chamber is complete with a fan assembly for air recirculation and convection heating to 1200°F. An economical means to heat treat in-house and save time, cost, improve quality and control production. Available in 4 standard sizes, completely wired and assembled. Shipped ready for startup.

Standard Features

- Welded one piece shell construction for extra strength
- Heavy gauge heating elements in removable holders
- Energy efficient 4 ½" walls of insulation
- Hearth plates to support workload and protect floor brick
- Stainless steel fan in lower chamber for uniform low temp heating
- Horizontal swing doors with adjustable latch provides positive seal
- Safety switches shut off power when doors open
- Honeywell digital temperature controls in separate NEMA 1 panel

Model Specifications

| MODEL | CH/ H" | AMBI W" | ER L" | OVI H" | ERAI W" | L" | KW | VOLTAGE | WEIGHT (LBS) |
|-----------|-----------|------------|----------|-----------|------------|----|------|----------|--------------|
| RD8-H14 | 9 | 12 | 14 | 62 | 30 | 36 | 7 | 230/1/60 | 800 |
| RD8-H21 | 9 | 12 | 21 | 62 | 30 | 36 | 9.5 | 230/1/60 | 860 |
| RD8-KHE18 | 12 | 14 | 18 | 62 | 32 | 36 | 10.5 | 230/1/60 | 920 |
| RD8-KHE24 | 12 | 14 | 24 | 62 | 32 | 36 | 12 | 230/1/60 | 980 |

Options: Over temperature safety system - fusible disconnect switch - vertical lift door 12 hour soak timer - rollaway quench tank - heat treat foil – gloves – tongs 3 phase wiring - 460 volts

2048 Bunnell Road - Warrington, PA 18976 info@luciferfurnaces.com

Tel: 800-378-0095

www.luciferfurnaces.com